



## Panoramic High Definition IP Dome Cameras with High Definition Stream Management (HDSM)

| Key Features   | Benefits   |
|--|--|
| <ul style="list-style-type: none"> <li>• Panoramic Wide Area Coverage</li> </ul>             | <ul style="list-style-type: none"> <li>• Four sensors provide 180° or 360° coverage of large areas in high definition from a single camera</li> </ul>  |
| <ul style="list-style-type: none"> <li>• Easy Installation</li> </ul>                        | <ul style="list-style-type: none"> <li>• Pre-focused lenses factory installed, no lens adjustment required during installation</li> </ul>  |
| <ul style="list-style-type: none"> <li>• Compact Ruggedized Dome Form Factor</li> </ul>      | <ul style="list-style-type: none"> <li>• Vandal Resistant , water proof, and dustproof</li> <li>• Versatile 3-axis adjustment for simple mounting in any configuration</li> <li>• Mounting accessories for in-ceiling, electrical box, and outdoor environments</li> </ul> |
| <ul style="list-style-type: none"> <li>• Multi-Megapixel</li> </ul>                          | <ul style="list-style-type: none"> <li>• Capture high quality detailed images</li> <li>• Reduce total number of cameras</li> <li>• Live and post-incident digital PTZ</li> </ul>   |
| <ul style="list-style-type: none"> <li>• High Definition Stream Management (HDSM)</li> </ul> | <ul style="list-style-type: none"> <li>• Highest possible quality recording with no loss of data</li> <li>• Dynamically controlled bandwidth utilization for optimal streaming</li> </ul>  |
| <ul style="list-style-type: none"> <li>• Alarm Input and Outputs</li> </ul>                  | <ul style="list-style-type: none"> <li>• Synchronize recording with external alarms and integrate camera motion detection into your current alarm system</li> </ul>  |
| <ul style="list-style-type: none"> <li>• Power-over-Ethernet (PoE)</li> </ul>                | <ul style="list-style-type: none"> <li>• No external power required</li> </ul>   |
| <ul style="list-style-type: none"> <li>• Plug-and-Play</li> </ul>                            | <ul style="list-style-type: none"> <li>• Auto-detection and auto-configuration of cameras for easy installation</li> </ul>   |
| <ul style="list-style-type: none"> <li>• Audio Recording</li> </ul>                          | <ul style="list-style-type: none"> <li>• Record high quality audio from any line input or microphone source</li> </ul>   |





# Panoramic High Definition IP Dome Cameras with High Definition Stream Management (HDSM)


| Resolution | Pixel Layout           | Sensor Format | Lens            | Maximum Images Per Second      | Camera Type               | Sensitivity (lux) | Model             | Recommended Application  |
|------------|------------------------|---------------|-----------------|--------------------------------|---------------------------|-------------------|-------------------|--|
| 8.0 MP     | 1600 x 1200 per sensor | 4 - 1/4"      | 4 - 4.4mm f/2.0 | 7 ips (28 ips for all sensors) | 180° Panoramic Color Dome | 0.6 in Color      | 8.0MP-HD-DOME-180 | Complete high definition coverage of a 180° wide field of view from a single camera without any distortion |
| 8.0 MP     | 1600 x 1200 per sensor | 4 - 1/4"      | 4 - 2.4mm f/2.0 | 7 ips (28 ips for all sensors) | 360° Panoramic Color Dome | 0.6 in Color      | 8.0MP-HD-DOME-360 | Complete 360° high definition coverage of a room from a central mounting point using a single camera       |

## Panoramic HD IP Dome Camera Options

| Model No. | Descriptions                  |
|-----------|-------------------------------|
| -H        | Factory installed heater unit |

## Panoramic HD IP Dome Camera Accessories


| Model No.     | Descriptions   |
|---------------|--|
| DOME-INDE-PLT | Indoor electrical box mounting plate, allows surface mounting with side cable access and mounting to an electrical box                 |
| DOME-OD-BASE  | Outdoor mounting base, creates an IP66 sealed enclosure for outdoor environments   |
| DOME-OD-PEND  | Outdoor pendant mount, creates an IP66 enclosure for connection to industry standard pendant mounts                                    |
| PEND-GS-WALL  | Gooseneck wall bracket for use with DOME-OD-PEND   |
| DOME-IND-CEL  | In-ceiling mount allows the camera to be ceiling mounted with only the external dome cover showing                                     |
| IND-CEL-PNL   | Metal ceiling panel for use with the DOME-IND-CEL to replace or reinforce the existing ceiling tile in suspended ceiling installations |
| DOME-SMOKE    | Replacement smoked transparent cover.  |




DOME-INDE-PLT



DOME-OD-BASE



DOME-OD-PEND



DOME-IND-CEL

All Avigilon HD IP Dome Cameras have DC auto-iris control and can be powered by PoE, AC or DC. Product specifications subject to change without notice.